



PICASSO LIGHTING INDUSTRIES, LLC
320 West Commerical Ave., Moonachie, NJ 07074
201.246.8188

Indoor Distribution Test Report

Picasso Lighting Industries, LLC

320 West Commerical Ave.
Moonachie, NJ 07074

Photopia Photometric Analysis & Optical Design

Catalog Number

MUS-xR-4-D10-I10-30-80-FW-BW-W

MUSE - 4' Up/Downlight - White Housing, Frosted White Lens (Downlight), Bat Wing Lens
(Uplight)

Test Number

IES-P00377

Test Date

Fri Oct 01 11:30:58 2021

The results contained in this report pertain only to the tested sample.
This report shall not be reproduced, except in full, without written approval of Picasso Lighting Industries, LLC.

MUS-xR-4-D10-I10-30-80-FW-BW-W
MUSE - 4' Up/Downlight - White Housing, Frosted White Lens (Downlight), Bat Wing Lens
(Uplight)
LED (3000K 80+ CRI)



Image may differ slightly from actual unit.

Summary of Results

Output:

Watts:	68.79 W
Lumens:	8,149.60 lm
Efficiency:	N/A
Efficacy:	116.5 lm/W

Spacing Criterion


Two luminaires, plane 0°	1.24
Two luminaires, plane 90°	1.21
Four luminaires	1.34

Full Beam Angle

0° - 180°	286.1°
90° - 270°	227.8°

Calculated results may not be representative of field performance.
Ballast factors have not been applied.

Candela Polar Plot



Zonal Lumen Summary

Zone	Lumens	% Fixture	Zone	Lumens	% Fixture
0° - 10°	255.88	3.14%	90° - 100°	112.01	1.37%
10° - 20°	402.00	4.93%	100° - 110°	344.52	4.23%
20° - 30°	608.61	7.47%	100° - 120°	947.84	11.63%
30° - 40°	726.05	8.91%	120° - 130°	750.13	9.20%
40° - 50°	737.33	9.05%	130° - 140°	720.36	8.84%
50° - 60°	639.06	7.84%	140° - 150°	600.33	7.37%
60° - 70°	445.74	5.47%	150° - 160°	457.58	5.61%
70° - 80°	217.98	2.67%	160° - 170°	288.34	3.54%
80° - 90°	61.77	0.76%	170° - 180°	178.60	2.19%
0° - 90°	4,094.42	50.24%	0° - 180°	8,149.60	100.00%



Candela Distribution

	0.00°	22.50°	45.00°	67.50°	90.00°
0.00°	1,515.66	1,515.66	1,515.66	1,515.66	1,515.66
10.00°	1,470.13	1,469.14	1,471.26	1,471.49	1,477.14
20.00°	1,396.93	1,396.32	1,402.08	1,400.87	1,399.01
30.00°	1,275.52	1,272.58	1,271.70	1,255.98	1,248.59
40.00°	1,098.56	1,101.45	1,081.47	1,056.23	1,048.63
50.00°	892.02	888.15	854.44	819.82	806.77
60.00°	649.17	634.68	589.64	552.98	540.50
70.00°	377.51	356.07	314.16	283.37	272.59
80.00°	133.54	118.60	94.00	79.80	75.09
90.00°	15.58	19.94	17.13	10.58	10.10
100.00°	91.87	150.51	236.89	231.08	209.84
110.00°	232.84	328.02	551.11	590.98	570.40
120.00°	387.74	493.34	811.75	1,033.35	1,050.77
130.00°	557.46	645.09	904.72	1,202.64	1,329.32
140.00°	717.71	770.09	936.90	1,112.62	1,205.82
150.00°	849.15	872.26	984.33	1,064.39	1,126.69
160.00°	951.51	966.79	1,016.34	1,059.32	1,079.26
170.00°	1,028.30	1,020.35	1,032.42	1,042.32	1,054.11
180.00°	1,049.14	1,049.14	1,049.14	1,049.14	1,049.14

Average Luminaire Luminance [cd/m²]

	0.00°	45.00°	90.00°
0.00°	12,110	12,110	12,110
45.00°	10,389	6,195	5,241
55.00°	9,603	4,805	3,864
65.00°	8,246	3,234	2,444
75.00°	6,032	1,634	1,134
85.00°	3,518	522	314



Coefficients of Utilization – Zonal Cavity Method

Values are lumens delivered to the workplane.

RCR	pfc	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
	pcc	80%	80%	80%	80%	70%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
	pw	70%	50%	30%	10%	70%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
	0	8,736	8,736	8,736	8,736	8,062	8,062	8,062	8,062	6,802	6,802	6,802	5,650	5,650	5,650	4,592	4,592	4,592	4,094
	1	7,993	7,646	7,336	7,057	7,365	7,070	6,804	6,563	5,991	5,800	5,624	5,000	4,867	4,743	4,087	3,998	3,914	3,486
	2	7,292	6,699	6,209	5,797	6,711	6,203	5,778	5,418	5,271	4,958	4,687	4,412	4,187	3,989	3,617	3,462	3,323	2,948
	3	6,662	5,903	5,315	4,847	6,128	5,473	4,959	4,545	4,664	4,277	3,959	3,915	3,632	3,394	3,221	3,020	2,848	2,517
	4	6,103	5,235	4,600	4,114	5,613	4,861	4,302	3,869	4,155	3,728	3,389	3,500	3,181	2,922	2,890	2,659	2,469	2,175
	5	5,610	4,674	4,021	3,538	5,161	4,347	3,768	3,335	3,728	3,280	2,936	3,152	2,812	2,545	2,613	2,364	2,164	1,902
	6	5,174	4,200	3,547	3,078	4,764	3,913	3,331	2,908	3,367	2,911	2,571	2,857	2,508	2,241	2,380	2,120	1,916	1,682
	7	4,789	3,798	3,156	2,706	4,413	3,544	2,969	2,560	3,060	2,605	2,274	2,607	2,254	1,991	2,181	1,916	1,713	1,502
	8	4,449	3,455	2,830	2,400	4,105	3,229	2,667	2,275	2,797	2,349	2,028	2,392	2,041	1,785	2,011	1,744	1,545	1,354
	9	4,148	3,160	2,555	2,147	3,831	2,958	2,412	2,039	2,571	2,132	1,824	2,207	1,861	1,613	1,864	1,598	1,404	1,230
10	3,880	2,906	2,323	1,935	3,589	2,724	2,196	1,841	2,376	1,948	1,653	2,047	1,707	1,468	1,736	1,474	1,284	1,126	

Cone of Light

Mtg Height	Light Level	0°-180° Beam Diameter	90°-270° Beam Diameter
6 ft	42 fc	0 ft	0 ft
8 ft	24 fc	0 ft	0 ft
10 ft	15 fc	0 ft	0 ft
12 ft	11 fc	0 ft	0 ft
15 ft	7 fc	0 ft	0 ft